

Adding Barista Application Languages

For the Barista framework:

- the Barista menus - barista/sys/config/<lang>/barista.men and barista_dev.men
- ensure STBL("+DEV_MODE")="YES" and run "Create Locale Property Files" on a fresh Barista install, selecting all the Barista tables
- the Barista properties file barista/sys/prop/barista.properties, creating barista/sys/prop/barista_<iso-lang>.properties
- the appropriate decimal/grouping chars for the SETOPTS and the default date format in the Barista configuration – barista/sys/config/<lang>/barista.cfg
- the descriptive text for the "[CPTAddins]" block - barista/sys/config/<lang>/barista.cpt
- the descriptive text found in barista/sys/config/<lang>/barista.ini
- the addition of the language to the ADC_LANGUAGE table (check-in adc_language.dat)
- the inclusion of the language code in the "active locales" of the Barista module records in the ADM_MODULES table (check-in adm_modules.dat)
- rebuild all Barista framework forms and check-in the barista/sys/data/arc/<lang>/ and barista/sys/data/def/<lang>/ files
- add language code to "convertBaseArcs.bbj" found in the baristautils repository and run it – check-in resultant barista/sys/base/<lang>/ files

For a Barista application:

- the application menu(s) - <app>/config/<lang>/<app>.men
- add language code to list of locales in <app>/config/<app>.syn file – the language code must also exist in Barista's ADC_LANGUAGES table
- run "Create Locale Property Files", selecting all the application tables
- the application properties file <app>/prop/<app>.properties, creating <app>/prop/<app>_<iso-lang>.properties
- update any start script/desktop link with new language code (e.g. -IENU;ESP;FRA)
- rebuild all application forms and check-in the <app>/data/arc/<lang>/ and <app>/data/def/<lang>/ files, if needed (Examples yes, Addon no)

For BBj:

- Update the following repositories:
 - o [svn://svn.basis.com/bbj/trunk/com/basis/bbj/web/gwt/client/i18n](https://svn.basis.com/bbj/trunk/com/basis/bbj/web/gwt/client/i18n)
 - o [svn://svn.basis.com/bbj/trunk/com/basis/bbj/web/gwt/client/resources](https://svn.basis.com/bbj/trunk/com/basis/bbj/web/gwt/client/resources)
 - o [svn://svn.basis.com/bbj/trunk/com/basis/install/prompts](https://svn.basis.com/bbj/trunk/com/basis/install/prompts)